

**Proud And
Independent Riders Wanted**



Friends gather.

Freedom calls.

The road beckons.

Your GSR750 awaits you.



Glass Sparkle Black (YVB)

Glass Sparkle Black / Pearl Mira Red (JSP)

Pearl Glacier White (YWW)

GSR750/A SPECIFICATIONS

Engine type	4-stroke, 4 cylinder, liquid-cooled, DOHC	
Bore x Stroke	72.0 mm x 46.0 mm	
Displacement	749 cm ³ (cc)	
Compression ratio	12.3	
Fuel system	Fuel injection	
Oil capacity (Overhaul)	3.9L (4.1 US qt.)	
Ignition system	Electronic ignition (Transistorized)	
Starter system	Electric	
Lubrication system	Wet sump	
Transmission	6-speed constant mesh	
Primary reduction ratio	1.857 (78 / 42)	
Final reduction ratio	2.470 (42 / 17)	
Rake / Trail	25°15' / 102 mm (4.0 in.)	
Suspension	Front	Inverted telescopic, coil spring, oil damped
	Rear	Link type, coil spring, oil damped
Wheels	Front	17M/C x MT3.50, Cast aluminum alloy
	Rear	17M/C x MT5.50, Cast aluminum alloy
Brakes	Front	Disc, twin
	Rear	Disc
Tires	Front	120/70ZR17M/C (58W), tubeless
	Rear	180/55ZR17M/C (73W), tubeless
Fuel tank capacity	17.5 L (4.6 US gal.)	
Overall length	2,115 mm (83.3 in.)	
Overall width	785 mm (30.9 in.)	
Overall height	1,060 mm (41.7 in.)	
Wheelbase	1,450 mm (57.1 in.)	
Ground clearance	145 mm (5.7 in.)	
Seat height	815 mm (32.1 in.)	
Curb mass	211 kg (465 lbs.) / 215 kg (474 lbs.)	